



ISUNA | 10+ years in storage inverter

Sinexcel

Stock Code:300693



RESIDENTIAL Storage Inverter



Solar+Storage Hybrid Inverter



High Efficiency



Multi-unit Parallel



Wide Range of Power



Strong Battery Voltage Compatibility



VPP Interface Ready

01

Single / Three Phase Hybrid Inverter

Higher Reliability

- IP65 Outdoor&Indoor use
- Natural cooling, Ultra silence
- SiC technology, Longer lifespan
- Plug-in design, Easy to install

High Capability

- 15 units in parallel
- 2 independent ports for battery
- Support mixture use of old & new battery

- Auto sleep
- VPP interface ready
- Cloud + Smart data analysis

Smart Monitoring

- UPS function
- Flexible DO control
- 10ms on/off-grid switchover
- 100% three phase unbalance

Strong Load Adaptability



02

Typical Configuration



Three Phase Datasheet

Model Name	Isuna 10000T	Isuna 12000T	Isuna 15000T	Isuna 18000T	Isuna 20000T
Off-grid Output					
Nominal Output Power	10kW	12kW	15kW	18kW	20kW
Nominal Voltage	3/N/PE, 220/380Vac, 230/400Vac				
Nominal Frequency	50/60Hz				
Output THDu	<3%				
Nominal Output Current	15A	18A	22.5A	27A	30A
On-grid Parameter					
Nominal Output Power	10kW	12kW	15kW	18kW	20kW
Max. Output Power	11kVA	13.2kVA	16.5kVA	19.8kVA	22kVA
Max. Input Power from Grid	20kVA	24kVA	30kVA	36kVA	40kVA
Max. Input Current from Grid	29A	35A	44A	52A	58A
Max. Output Current	16A	20A	24A	29A	32A
Nominal Grid Voltage	3/N/PE, 220/380V, 230/400V, 240/415V				
Grid Voltage Range	184-276V/320-480V				
PV Input					
Max. Input Power	15000Wp	18000Wp	22500Wp	27000Wp	30000Wp
Max. Input Voltage	1000V				
Number of MPPTs	2				
Max. Input Strings Per MPPT	2				
MPPT Voltage Range	180-960V				
Full Load MPPT Voltage Range	250-850V	290-850V	350-850V	410-850V	450-850V
Nominal Input Voltage	600V				
Starting Voltage	200V				
Max. Input Current	25A/25A				
Short-Circuit Current	30A/30A				
Battery Parameter					
Battery Type	Lithium-ion				
Number of Battery Input	2				
Battery Voltage Range	180-800V				
Full Load Battery Voltage Range	210-800V	250-800V	300-800V	360-800V	400-800V
Peak Charging/Discharging Current & Duration	35A/35A(60s)				
Max. Charging/Discharging Current	25A/25A				
Efficiency					
Max. Efficiency	98.20%				
European Efficiency	97.70%				
Max. Battery Charging/Discharging Efficiency	97.80%				
General Data					
Size(W*H*D)	573mm*509mm*219mm				
Weight	35kg				
Noise	<45db(A)				
Operating Temperature Range	-25°C~+60°C				
Cooling Method	Air Cooling				
Ingress Protection Grade	IP65				
Communication Port	RS485/CAN/DRED/Dry contact/Parallel port				
Monitoring	LED/APP/WIFI/4G/Bluetooth				
Protection	DC Switch, AC Overvoltage Protection, AC Overcurrent Protection, AC Short Circuit Protection, Anti-islanding Protection, Residual Current Monitoring, PV Insulation Resistance Detection, Surge Protection:LEVEL II, Reverse Polarity Protection(PV&Battery);Lightning Protection				
Certification					
CE_LVD	IEC 62109-1, IEC 62109-2, EN 62109-1, EN 62109-2				
CE EMC	EN61000-6-1, EN61000-6-2, EN61000-6-3, EN61000-6-4				
Grid	VDE-AR-N 4105, C10-11, G98/G99, CEI 0-21, EN50549, NRS 097-2-1, AS 4777.2, R25,UNE217001,UNE217002,NTS 2.1				