

Residential LFP Battery Series

Lithiumalley

LV-BAT-W10.24Ac

51.2V 200Ah 10.24kWh

A sleek and space-saving solution for your energy storage needs. With its compact design and easy installation, it seamlessly blends into any environment. Whether in your home, office, or commercial space, our wall-mounted unit provides reliable and efficient energy storage.







LV-BAT-W10.24Ac is a perfect wall-mounted solar energy lithium battery for residential home use. Built-in with High-Quality LiFePO4 large capacity cells. It ensures a long cycle life of the battery system. The designed BMS is verified to be compatible with different brands of inverters, hybrid on grid&off grid or off grid.

DONGUAN LITHIUM VALLEY ENERGY CO., LTD .

FEATURES



Unique Design New wall mount design

SOC, Battery Status





Flexible Capacity Max.15pcs in Parallel to extend capacity

Quick plug in +/- and

parallel connection





Safe & Reliable Lithium Iron Phosphate (LFP) Cell

Certificates CB, IEC62619, UL1973, UKCA, CE-EMC, CE-GPSD, EN62619 ; UN38.3, MSDS

Dimensions







| Model | LV-BAT-W10.24Ac |
|----------------------------------------------|-----------------------------------------------------------------------------|
| Nominal Voltage | 51.2V |
| Rated Capacity | 200Ah |
| Energy | 10240Wh |
| Charging Cut-off Voltage | 56.16V |
| Discharge Cut-off Voltage | 45.6V |
| Recommend charge/discharge current | 100A |
| Maximum continuous charge/discharge current | 200A |
| Instantaneous discharge current | 400A/3S |
| Charge temperature | 0~55°C |
| Discharge temperature | −20~60°C |
| Storage Environment (50% state of charge) | 20°C ~ 45°C in three months; 25±3°C over three months; Humidity:65±20%RH |
| Environment | Indoor |
| Installation | Wall mounted |
| Cell Technology | Lithium iron phosphate (LiFePO4) |
| Life Cycle | 6000 times @80%DOD |
| Cooling | Natural convection |
| Protection Rating | IP65 |
| Certificates | CB, IEC62619, UL1973, UKCA, CE-EMC, CE-GPSD, EN62619 ; UN38.3, MSDS |
| Dimension and Weight | |

Dimension

Battery Net Weight/Gross Weight

Communication Instruction

Communication

RS232, CAN, RS485

800*590*142mm

98KG/106KG



Factory Address: No. 11, Yinyang Road, Zhangyang Community, Zhangmutou Town, Dongguan

